

CLAIM AMENDMENTS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended). A mailing machine assembly, comprising:

a mailing machine including a controller, a security module connected to said controller, and a non-removable program memory operationally connected to said security module and configured to store an initialization program; and

a removable authorization device for providing an authorization of an initialization of said mailing machine, said authorization device being operationally connected to said mailing machine ~~and configured for being interrogated by said mailing machine~~; and

said security module being programmed to check whether ~~authorization is present~~ said authorization device has provided the authorization of the initialization of said mailing machine and ~~for preventing an~~ to prevent the initialization of said mailing machine without authorization from said authorization device;

wherein the initialization includes inputting initialization data to said mailing machine.

Claim 2 (previously presented). The mailing machine assembly according to claim 1, wherein said authorization device is indirectly connected to said mailing machine via a data source selected

from a group consisting of a personal computer, a laptop, and a remote data center.

Claim 3 (original). The mailing machine assembly according to claim 1, wherein said authorization device is directly connected to said mailing machine.

Claim 4 (previously presented). The mailing machine assembly according to claim 2, wherein said mailing machine is a franking machine having a meter with a user interface, for a data input of predetermined values, and a postal security device configured to check an authorization of the data input.

Claim 5 (original). The mailing machine assembly according to claim 4, wherein said franking machine has a base with a first interface for attachment of said data source containing initialization data for said mailing machine, and a second interface for attachment of said authorization device.

Claim 6 (original). The mailing machine assembly according to claim 5, wherein said authorization device is a dongle.

Claim 7 (original). The mailing machine assembly according to claim 5, wherein said data source contains initialization data for said mailing machine and is configured to be attached to said first interface of said base of said mailing machine, and wherein said authorization device is a chip card and a chip card reader is operatively connected to said meter via a further internal interface and arranged to be integrated into said base.

Claim 8 (original). The mailing machine assembly according to claim 5, wherein said first, second and further interfaces of said mailing machine are serial interfaces.

Claim 9 (previously presented). The mailing machine assembly according to claim 4, wherein said interface is a serial interface.

Claim 10 (original). The mailing machine assembly according to claim 5, wherein said first interface of said base of said mailing machine is configured for attachment of said data source, said authorization device is connected to said data source via a parallel interface, said data source is a computer and is coupled via a serial interface of said mailing machine, and wherein a chip card reader is integrated and operatively connected to said meter via an interface of said meter.

Claim 11 (original). The mailing machine assembly according to claim 1, wherein said mailing machine is a franking machine with a meter and a chip

card reader integrated in said meter and coupled to a parallel bus of said meter via an interface and wherein said authorization device is a chip card.

Claim 12 (original). The mailing machine assembly according to claim 1, wherein said mailing machine is a set of scales, and wherein a chip card reader is integrated into said scales and coupled via an interface of said scales, and wherein said authorization device is a chip card.

Claim 13 (previously presented). The mailing machine assembly according to claim 1, wherein said mailing machine has a modem and a modem interface for loading therethrough the initialization data or values, and wherein said authorization device is an insertable chip card, for authorizing at least that part of the initialization data which are loaded into said mailing machine from a data source via said modem interface.

Claim 14 (original). The mailing machine assembly according to claim 1, wherein said mailing machine is a franking machine having at least one program memory with an initialization program and a postal security module, for checking the authorization before and during the initialization, and wherein said postal security module is configured for loading initialization data.

Claim 15 (original). The mailing machine assembly according to claim 14, wherein a checking of the authorization before and during the initialization is performed on the basis of a unique authorization number, input via a dongle or

a chip card and wherein the authorization is given if the unique authorization number input into the mailing machine has a predetermined relationship with a number stored in said postal security module.

Claim 16 (original). The mailing machine assembly according to claim 1, which comprises a program memory at least partly storing the initialization program, said program memory forming a component part of said security module, and including a separate program memory operatively in connection with said security module and storing another part of the initialization program.

Claim 17 (original). The mailing machine assembly according to claim 16, wherein the other part of the initialization program is for initialization data stored in a non-volatile manner externally of the security module.

Claim 18 (currently amended). A method of initializing a mailing machine, which comprises the steps of:

switching a mailing machine into an initialization mode;

~~authorizing an initialization~~ providing an authorization of an initialization of the mailing machine with an a removable authorization device and, wherein the initialization includes inputting initialization data to the mailing machine;

with a security module, checking the authorization provided by the authorization device with a security module, in order to prevent initialization of the mailing machine without the authorization;

~~if authorization is found~~ if the security module finds that the authorization device has provided the authorization, inputting initialization data at least partly supplied by an electronic data source to the mailing machine at least partly supplied by a data source; and

ending the initialization and cancelling of the authorization.

Claim 19 (original). The method according to claim 18, which comprises:

switching a franking machine into the initialization mode and establishing a connection to a data source;

authorizing initialization with an authorization device;

inputting a battery date BAT_DATE_SAD of a battery of the security module, a telephone number of the telepostage data center TDC of the destination country and a postage call-up number PAN;

transmitting a serial number SAD-SN of the security module to the telepostage data center TDC of the country, to initialize a comparison of the serial number SAD-SN sent with a stored serial number, and to generate a notification;

receiving the notification sent by the telepostage data center TDC in the franking machine and loading codes DES-Keys for credit recharging into the security module SAD; and

terminating the initialization and cancelling the authorization by removing the authorization device.

Claim 20 (previously presented) The method according to claim 19, wherein the establishing step comprises connecting via a transmission device selected from a group consisting of a modem, a laptop, and a PC interface.

Claim 21 (original). The method according to claim 19, which comprises switching into the initialization mode at the goods receiving location in the destination country as a result of activating a means of activating a user interface and establishing a connection to a data source via a transmission device selected from the group consisting of a modem, a laptop, and a PC interface.

Claim 22 (previously presented). The method according to claim 19, comprising sending notification by the telepostage data center TDC including a code MAC-Key for a security imprint, which is received by the franking machine and loaded into the security module SAD.

Claim 23 (previously presented). The method according to claim 19, comprising providing the codes DES-Keys for credit recharging including the subcodes Key(0), Key(1), Kvar and loading the codes into the security module SAD.

Claim 24 (previously presented). The method according to claim 23, comprising sending the notification by the telepostage data center TDC including extra data stored in a non-volatile memory externally of the security module and including inkjet cartridge data.

Claim 25 (original). The method according to claim 18, wherein the inputting step comprises inputting initialization data with the chip card.

Claim 26 (previously presented). The method according to claim 18, comprising providing data input of extra data including inkjet cartridge data and storing the data in a non-volatile memory externally of the security module.

Claim 27 (previously presented). The method according to claim 18, which comprises interrogating the authorization device before and during the initialization of the mailing machine with predetermined data.